

MANUAL FOR CHANGING THE UV-C BULB

OZONOS AIRCLEANER

AC-I | AC-I PLUS | AC-I PRO



I. CHANGING THE UV-C BULB



I. In order to be able to work comfortably, place the device in this position on a stable surface on which the device cannot roll away.



2. Unscrew the two screws with a Torx IO screwdriver.



3. Put the outer case aside and unscrew the screw of the inner case.



4. Slide the case to the right, pull it up and set it aside for later use.



5. Now lift the lamp first on the left, then on the right side out of the bracket and carefully pull the lamp out of the plug.




6.6.Netwachte Sinedviel and participation of the unput segmetric finite drives vollständig in den Stecker ein.



7. Place the lamp first on the right (plug side) then on the left side of the bracket.



8. Slide the lamp towards the metal rod you see on the left.



9. Reassemble the inner case. Start by inserting the inner case as far to the right as possible and then slide it to the left. Now retighten the screw to fix the inner case.



10. Close the outer case and retighten the screws left and right.

IMPORTANT:

Please do not forget to reset the operating hours counter!

You will find the instructions on the next page!

2. RESETTING THE OPERATING HOURS COUNTER

Step by step manual:

- I. The device is disconnected from the power supply!
- 2. Keep button pressed and plug in the power plug at the same time.
- 3. While you keep the button on the device pressed and the device is connected to the power supply, press the "ON" button on the remote control.
- 4. As soon as the LED light of the button on the device starts flashing red (2Hz), the operating hours counter is successfully reset to 0.

